

#### PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M12.

MANUFACTURER:

**ALTRO LTD**

Works Road, Letchworth Garden City

Hertfordshire, SG6 1NW

Tel: 01462 707600

E-mail: [enquiries@altro.com](mailto:enquiries@altro.com)

Website: <http://www.altro.co.uk>

Supplier Contact: Altro Customer Care Centre [enquiries@altro.com](mailto:enquiries@altro.com)

#### PRODUCT DESCRIPTION

##### ICL APPROVED SPECIFICATION

**Range:** Altro Flow

**Description:** Solvent-free epoxy resin FeRFA type 5

**Application:** Areas of use pharmaceutical, industrial, production areas, areas requiring increased hygiene

**Other:** Four versions available

**1mm, 2mm, 3mm standard and a 3mm static dissipative variant.**

Altro Flow is a three-part solvent-free epoxy resin based self-smoothing floor topping, which produce a smooth, attractive and easily cleaned seamless floor. Altro Flow has a high gloss finish but can be sealed with Altro Seal™ water based matt for an aesthetically pleasing matt finish.

**Finish:** High Gloss finish

**Service Temperature:** 0-60C

**Chemical Resistance:** Good.

**Guarantee:** 6 year product guarantee.

#### TYPICAL NBS SPECIFICATION

**M12: 110a/b/c**

##### RESIN FLOORING

**Standard:** Approved Resin Flooring to Imperial College London Architectural Standards

**Location:** To architects finishes schedules.

**Base:** As per architects details., Typically sand/cement modified screed, concrete, timber or metal

**Priming:** Altro Prime consolidating

**Manufacturer:** Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW

**Range:** Altro Flow

**Type:** Epoxy Resin System FeRFA type 5

**Colour:** All colours approved.

**Moisture Content:** Substrate moisture content should not exceed 75% R.H. or 5% moisture content by weight.

**Free Edges:** Transition to abutting floor finishes: Straight and smooth. Surfaces should be primed using Altro Prime Standard. Where applicable suitable transition strip may be used between different surfaces

**Joints:** All vertical joints to be transferred through the cove detail and in-filled with Altro Expand vertical. (Altro Prime standard contact surfaces)