

**ARCHITECTURAL STANDARDS  
PRODUCT DATA SHEET**

**M50 FLOOR FINISHES**

**PREFERRED SUPPLIER INFORMATION**

NBS REFERENCE M50 / 130  
 MANUFACTURER: Amtico International  
 Address Solar Park Southside  
 Solihull B90 4SH  
 Tel 0121 745 0800  
 E-mail [samples@amtico.com](mailto:samples@amtico.com)  
 Website: [www.amtico.com](http://www.amtico.com)  
 Supplier: Contact: Shonagh Clayton



**PRODUCT DESCRIPTION**

ICL APPROVED SPECIFICATION

**Range:** Amtico Entryway - Recoarse  
**Type:** Entrance Matting Tile  
**Description:** Entryway is tough, resilient and protective, featuring reinforced scraper fibres to remove grit and moisture  
**Application:** Entrance areas approximately 2.5metre into building  
**Other:**  
**Environmental:** Complies with DiBT (20/10) for indoor use  
**Recyclable:** Contains some recycled content see website for info  
**Warranty:** 10 year commercial warranty  
**Production:** Designed & made by our parent company Mannington group

**TYPICAL NBS SPECIFICATION**

**M50?/130?** M50 available - contact the Amtico Technical Team  
**Standard:**  
**Location:**  
**Base:**  
 Subfloor & Preparation  
 Dust, dirt, debris, and old adhesive residues must be removed before installation begins. Surfaces must be sound, smooth and level with all holes and cracks filled with a suitable smoothing compound.  
**Preparation:** Subfloor surfaces must be tested for moisture content and should comply with the relevant local regulations, (UK) 75% RH  
 Note: Moisture in excess of the recommended levels can cause the adhesive to fail. This condition can result in shifting, peaking or edge curling of the tiles.  
**tiles description:** 8.7mm thick Entrance Barrier Matting Tile  
**Manufacturer:** Amtico International  
**Product reference:** Amtico Entryway  
**Size:** 609.6 x 609.6mm / 24" x 24"  
**Type:** Entrance Barrier Matting Tile  
**Colour/Pattern:** Black, Grey, Brown  
**BS EN Classification:** EN 1307

**ARCHITECTURAL STANDARDS  
PRODUCT DATA SHEET**

**M50 FLOOR FINISHES**

<b>Category:</b>	Textile Floor Coverings
<b>Level of use Class:</b>	EN 1307 - 33 Luxury Class 4
<b>Method of laying:</b>	Bonded, suitable adhesive dependant on location
<b>Setting out:</b>	See laying pattern information on website
<b>Accessories:</b>	
<b>Special requirements:</b>	
<b>Tile backing:</b>	Vinyl