

<b>ARCHITECTURAL STANDARDS</b>	<b>CEILING FINISHES</b>
<b>PRODUCT DATA SHEET</b>	
<b>SECTION 9: CEILINGS</b>	<b>K40</b>

**PREFERRED SUPPLIER INFORMATION**

NBS REFERENCE K40

MANUFACTURER:

**ARMSTRONG CEILINGS**

Address Harman House, 1 George Street  
Uxbridge, Middlesex UB8 1QQ

Tel 07917843941 / 0800371849

Fax 01895258188

Website: [www.armstrong-ceilings.co.uk](http://www.armstrong-ceilings.co.uk)

Supplier:

Contact: Karamjit Sidhu <KSidhu@armstrongceilings.com>



**PRODUCT DESCRIPTION**

ICL APPROVED SPECIFICATION

Range: Bioguard Plain

Product Code BP2221

Description: Smooth Textured mineral fibre tiles with Anti-Microbial Paint treatment

Styles Tegular and Microlook edges available

Application Halls of Residence/ Food Preparation/ Labs & Medical Areas/Kitchen

Material Mineral Fibre

Size 600 x 600 mm

other Features Highly Cleanable / High light Reflectance/ Clean Room Performance ISO 5 rated

Environmental 43% Recyclable Content/ Tested against EN13964 - E1 rating for Emissions

Guarantees 15 Year Manufacturers Guarantee

Production: Made in Munster Germany

**TYPICAL NBS SPECIFICATION**

**K 40 CEILING TILE**

Standard: Approved ceiling installation to Imperial College London Architectural Standards

Range Bioguard Plain

Manufacturer: Armstrong Ceilings , Harman House, 1 George Street, Uxbridge Middlesex, UB8 1QQ

Colour/Pattern: Armstrong Global White

Ceiling Type Smooth textured mineral fibre tiles with Anti- Microbial Paint Treatment

Grid spacing 600 x 600 mm

Access Infill Units Fully Demountable 217 Suspension System Trulok Prelude Suspension System

Top Fixings As recommended by ceiling contractor

Hangers Trulok BP AW950 Suspension Wire

Grid Type Exposed 24 mm Grid System 219 Perimeter Trims Trulok Perimeter Trim BP T 1932H

Fixings (perimeters) As recommended by ceiling contractor

Fixing (centres) (maximum) 450 mm

