Imperial College London

London		
ARCHITECTURAL STANDARDS		
PRODUCT DATA SHEET		
N13: SA	NITARYWAR	E N13/300/SHEET 003/11
PREFFERED SUPPLIER INFORMATION		
NBS REFERENCE N13/300		
MANUFACTURER:		
IDEAL STANDARD (UK) L		TD
Address		orks, National Avenue
Address		
Tal	Kingston upon Hu	JII NOS 4NS
Tel	0870 122 8282	
E-mail	info@idealspec.co.	
Website:	www.idealspec.co.	<u>uk</u>
PRODUCT DESCRIPTION		
ICL APPROVED SPECIFICATION		
Range:	Alto	
Туре:	Wall mounted W	C
Description:	Short projection,	wall mounted WC pan with wash down action and box flushing rim
Use	Suitable for comm	nercial and domestic use
Material	Vitreous china to	BS 3402, BS EN 997 and BS EN 33
Cistern	Concealed	
Recyclable:		
Warranty:		nanufacturing or material defect
•	•	
Production: Made in the UK		
TYPICAL NBS SPECIFICATION		
N13:300		
Standard:	Approved WC Pa EN 997 and BS E	n/Cistern to Imperial College London Architectural Standards, BS3403, BS
Type: Short projection, wall mounted WC pan with wash down action and box flushing rim		
PAN	enert projection,	
Product refe	rence.	R3419. Alto wall mounted WC pan with wash down action and box flushing rim
Material		Vitreous china to BS 3402, BS EN 997 and BS EN 33
SEAT & COVER		
Manufacturer:		Ideal Standard (UIV) Ltd. National Avenue, Kingston upon Liul LIUE (US
Product reference:		Ideal Standard (UK) Ltd, National Avenue, Kingston upon Hull HU5 4HS
Material		E7590 Alto seat and cover with stainless steel hinges
Finish & Colour		Plastic
		White
PAN CONNECTOR Standard:		To BS5627, colour to match pan. Panekta reference S4305 for P trap and S4300 for S trap or P trap
Manufacturer:		Ideal Standard (UK) Ltd, National Avenue, Kingston upon Hull HU5 4HS
Colour		White
BRACKETS:		E0060 pair of support brackets for for load bearing walls up to 150mm thick and 145mm long to suit partitions 13-25mm thick
ACCESSORIES:		Support brackets screwed to floor within the duct. WC to be fixed to support brackets with bolts
		supplied and bolts screwed to back wall with brackets
Jointing		Joint between WC pan and panel to be sealed with waterproof silicon sealant, colour White

Alternative Frame