

**ARCHITECTURAL STANDARDS
PRODUCT DATA SHEET
K30 PANEL PARTITIONS**

DEMOUNTABLE PARTITIONS
NBS K30 130

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE K 30 / 130

MANUFACTURER: **Komfort Partitioning Ltd**

Address **Unit 501, Axxess 10, Bentley Road South, Wednesbury. WS10 8LQ**

Tel 0121 232 2400

E-mail andy.kerry@komfort.co.uk

Website: komfort.co.uk

Supplier: Contact: Andy Kerry



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range:	Komfort Komfire 75 non fire rated to 30/30 fire rated
Product Code	System Components
Application:	demountable glazed and solid dry wall partition system
Material	Glass, aluminium plasterboard and insulation products
Size	Up to 4000mm high infinite length
Environmental	Can achieve Bream excellent environment status. SKA rated A+
Recycling	ISO14001
Guarantees	1 year
Production	UK manufacturing

TYPICAL NBS SPECIFICATION

K30 130	Panel Partitions
Range	Komfire 75
Manufacturer	Komfort Partitioning Ltd

Type	<p>Partition height: To suit floor to ceiling height of 2410mm</p> <ul style="list-style-type: none"> - Deflection allowance: Not required • Panel type: Double glazed module • Solid panel finish/ colour: (ready for onsite decoration by others) • Glazed panels: <ul style="list-style-type: none"> - Glass: Acoustic laminate glass, /Toughened glass, 6 mm + laminated glass, 6.4 mm - Manifestation: (required if not having blinds) • Junction posts: <ul style="list-style-type: none"> - In line junction (solid panels): Clipped surface mounted trim (863) - Trim insert colour: (RAL0000) - 90° corner junction: Taped and jointed - Wall abutment: Channel (821) • Framework finish: Kolourframe polyester powder coated <ul style="list-style-type: none"> - Colour: (BS 4800 ref ___ /RAL ref ___ /Velocity Grey /Velocity White /Self coloured) • Skirtings: Aluminium, 75 mm, high square top edge, screw-fix <ul style="list-style-type: none"> - Colour: (Self-coloured /Black /Brown /Grey /White) • Incorporated features: <ul style="list-style-type: none"> - Door: - Type: Hollow core
Size	2040 mm x 826 mm x 44 mm

ARCHITECTURAL STANDARDS		DEMOUNTABLE PARTITIONS
PRODUCT DATA SHEET		
K30 PANEL PARTITIONS		<i>NBS K30 130</i>
Fire safety	Fully tested certification to 30/30 integrity and insulation	
warranty	Various but 1 year minimum	
Material /Finish	Glass . Aluminium Timber, plastic gaskets	
Recycling issues	Aluminium and glass have 50 year plus life cycle	
Enironmental issues	ISO14001 accredited, FSC accredited	
Maintenance issues	None	
Cleanability	simple damp cloth and window cleaning products	
Accoustic Properties	Acoustic insulation to BS EN ISO 140-3: 40 dB (Rw)	