

**ARCHITECTURAL STANDARDS
PRODUCT DATA SHEET**

Painting

M60 /Painting / Clear Finishing

M60 / 110

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M60 / 130

MANUFACTURER:

Crown Trade , Crown Trade Paints Ltd

Address


Crown House - Hollins Road, Darwen, Lancasher BB30BG

Tel 0044 (0) 3332227070

E-mail

Website: www.crownpaintspec.co.uk

Supplier: Contact: info@crownpaintspec.co.uk



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Matt Vinyl

Description: A highly durable premium quality matt emulsion for interior use on wall and ceiling surfaces, where a flat non-reflective finish is required

Application: For interior use only . Do not apply when air or substarte temperatures are likely to fall below 8 degrees centegrade or when the relative humidity is above 80% during application or the drying period

Other

Finish : Matt

Drying Time: under normal drying conditions touch dry in 1-2 hours and recotable after 4 hours. Allow for adequate vebtilation during the drying period

Packaging : 250ml, 1,2.5,5 and 10 litre

Wet film thickness 59 micrometres at 17 msq per litre and Dry film thickness 17 micrometres at 17 sqm per litre

This product will remail usable fir two years if stored correctly and unopened

TYPICAL NBS SPECIFICATION

M60 Painting / Clear Finishing - 110 Emulsion Paint

This product is associated with the following NBS clauses: M60 Painting/ Clear finishing - 110 Emulsion Paint

This product is associated with the following NBSCreate clause: 45 - 35 - 84/ 320 water-borne matt or flat finishes

Apply in accordance with BS 6150-2006 Code of Practice for painting of buildings and BS 8000:Part12:1989 Code of Practice for decorative wallcoverings and painting