

#### PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M50

MANUFACTURER:

**MILLIKEN CONTRACT**

Beach Hill Plant, Gidlow Lane, Wigan


Lancashire

WN6 8RN

Tel: +44 (0)1942 826073 Fax: +44 (0)1942 826570

Website: [www.milikoncarpeteurope.com](http://www.milikoncarpeteurope.com)

Supplier Contact: **Matt Tombs** [Matt.tombs@milliken.com](mailto:Matt.tombs@milliken.com)



#### PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION



Range: ~~Laylines~~

Styles: ~~Laylines Brights/ Laylines Neutrals~~

Application: Heavy contract use.

Construction: Tufted, Level Loop Pile

Total Thickness: 8.4 mm

Tile Size: 457.2 x 457.2 mm

Standard Backing: 85% Recycled content Polyurethane cushion. Available with TractionBack® on request.

Face Fibre: 100% Milliken-Certified WearOn® Type 6,6 Nylon

Environmental: 85% Recycled content cushion backing, 12% Recycled content by total product weight. Manufactured using electricity from renewable sources. Carbon Neutral certification. GUT & CRI Green Label Plus certified for indoor air quality. BRE Certification.

Recycling: 85% Recycled content Polyurethane cushion. 12% Recycled content by total product weight.

Guarantees: 12 year wear guarantee, Lifetime Antistatic guarantee, Latent Defects guarantee.

Production: Made in the UK

#### TYPICAL NBS SPECIFICATION

M50/130

**CARPET TILING**

Standard: Carpet tiling to Imperial College London Architectural Standards.

Location: See architects drawings and finishes schedules.

Base: Raised access floor or cement screed as architects drawings.

Preparation: Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. - Fabricated Underlay: N/A. Carpet tiles to be adhered direct to the subfloor. As clauses 410/420/430/440 and 460.

Carpet Tiles:

Manufacturer: Milliken Contract, Beach Hill Plant, Gidlow Lane, Wigan Lancashire WN6 8RN

Product reference ~~Laylines~~

Size: 457.2 x 457.2 mm

Type: Tufted, Level Loop Pile

Colour,/pattern: To architects finishes schedules.

BS EN 1307 Classification:

Category: General Contract

Level of use Class: Class 3, Heavy Use.

Method of laying: Fully bond with release adhesive as recommended by manufacturer.

Setting out: As clause 610.

Accessories: Edging strip at thresholds

Special requirements: Carpet tiles to be set out so that joints do not fall on raised floor tile joints.

Carpet backing: to be recyclable.

