

PREFERRED SUPPLIER INFORMATION

M12

MANUFACTURER: Sika Ltd
Address Head Office, Watchmead, Welwyn Garden City, Herts, AL7 1BQ
Tel 01707 394 444
E-mail Sales@uk.sika.com
Website: <http://GBR.Sika.com>
Supplier: Contact:



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Sikafloor - 263 SL
Product Code
Application: Serrated Trowel & Spike Roller
Material 2 Part Epoxy Self-Smoothing and Broadcast system
Size 20kg
Other Cleanroom Suitable
Environmental Conforms to the requirements of LEED
Guarantees Dependant on Job
Production Dependant on colour, 3 working days.

TYPICAL NBS SPECIFICATION

M12 M12 Specification - Resin Flooring
Standard ICL Approved Standard
Product Description
Manufacturer Head Office, Watchmead, Welwyn Garden City, Herts, AL7 1BQ
Product Reference Sikafloor - 263SL
Type
 2 Part Epoxy Self-Smoothing and Broadcast system, Cleanroom Certified.
 Must have all spillages removed immediately and must be regularly cleaned using rotary brush, mechanical scrubbers, scrubber dryer, high pressure washer, wash and vacuum techniques etc. using suitable detergents and waxes
Fire safety Fire classification in accordance with EN 13501-1, Report- No. 2007-B-0181/14, MPA Dresden, Germany, February 2007
warranty Dependant on Job
Size 20kg
Material /Finish Gloss
Enironmental issues The maximum content of Sikafloor®-264 is < 500 g/l VOC for the ready to use product.
Uses
 Sikafloor®-263 SL may only be used by experienced professionals.
 Self-smoothing and broadcast systems for concrete and cement screeds with normal up to medium heavy wear e.g. storage and assembly halls, maintenance workshops, garages, loading ramps etc.
 The broadcast system is recommended for multistorey and underground car parks, maintenance hangars and for wet process areas, e.g. beverage and food industry.
Cleanability As above

