

**ARCHITECTURAL STANDARDS
PRODUCT DATA SHEET**

Doors

L20 Doors

L20/545

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE L20/545

MANUFACTURER: SWG

Address Trastvagen 2, 890 51 Langviksmon, Sweden

Tel 0046 0662 30265

E-mail info@swg.nu

Website: www.swg.nu

Supplier: Contact: **Style Door Systems Ltd - south@style-partitions.co.uk -**

01202 874044 - Mark Atkins or Martin Lester



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Stylefold

Product Code 120/900

Application:

Material Range of finishes available to suit client requirements

Size Bespoke to fit site dimensions

Other

Environmental ISO 14001 (declaration available on request)

Recycling Majority of product manufactured from recyclable timber

Guarantees 2 year warranty subject to correct servicing

Production System manufactured in Langviksmon, Sweden

TYPICAL NBS SPECIFICATION

L20/545 Sliding Folding Partition - Manually Operated

Standard ICL Approved Standard

Range

Manufacturer SWG

Standard

Product Reference Stylefold 120/900

Type

Characteristics: 65mm/ 100mm thick manually operated flat panel continuously hinged system with internal espagnolette locking mechanism. Timber constructed panels with flush fitting protective aluminium edge profiles. Double three pronged rubber seals to top and bottom of each panel and 'D' seals in vertical profiles.

Track & Roller System: Top hung heavy duty extruded aluminium track complete with pelmets/suspension system. Centrefold, without floor guide or Endfold, complete with floor guide / Bottom rolling on a low profile surface mounted/recessed aluminium floor track. Centrefold/Endfold, complete with aluminium top guide track.

Arrangement: Bi-parting with leading panel out of each stack acting as a communicating door or stacking to one side only with leading panel out of stack acting as a communicating door.

Acoustic insulation: Ranging from 31dB Rw to 48dB Rw depending on system and thickness.

ARCHITECTURAL STANDARDS		Doors
PRODUCT DATA SHEET		
L20 Doors		<i>L20/545</i>
	<p>SWG Stylefold is moved manually and bolts operated with a removeable handle.</p> <p>For construction phase and long term repairs and maintenance manual handling is minimised due to maximum panel dimensions being more restrictive than other systems. Hinges etc are easily accessed and in the unlikely event panels are damaged very easy to replace.</p>	
Fire safety	Available in 30 minute or 60 minute fire rating if required.	
warranty	1 year warranty subject to correct servicing	
Size	Bespoke to fit site dimensions	
Material /Finish	Primed surface for on-site decoration by others/Melamine from the standard range/High pressure laminate/Wood veneer from the standard range (other finishes possible subject to feasibility)	
Recycling issues	Majority of product manufactured from recyclable timber	
Enironmental issues	Full environmental certification available subject to final finishes	
Source	System manufactured in Langviksmon, Sweden	
Maintenance issues	Full maintenance details to be supplied within O&M. Generally single service visit required per yesr depending on usage.	
Cleanability	Dependant on final finishes	
Other	Please contact local office for design assistance on individual projects.	