Imperial College

ARCHITECTURAL STANDARDS **PRODUCT DATA SHEET**

M60 / 160 M560 /Painting / Clear Finishing

PREFFERED SUPPLIER INFORMATION

NBS REFERENCE M60 / 160

MANUFACTURER:

Dulux Trade, Brand of AKZONOBEL

Address

Wrexham Road - Slough - SL2 5DS UK Tel 0044(0)3332227070

E-mail

Website: www.duluxtrade.co.uk

Supplier: Contact: Dulux.advice@akzonobel.com



Painting

PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION Range: Ultimate Woodstain

High performance olvent based exterior woodstain which produces a water repellent satin finish.

Description: Unique Ultimate wood protection technology - exterior joinery is protected from weather for up to 10

years if used in accordance with instructions.

Suitable for hardwood and softwoods . Solvent: low odour aliphatic hydrcarbons. Brush application. Application:

Not suitable for spraying. Touch dry 4 - 6 hours. Re-coat time - 16 hours

Other Pack sizes 2.5L and 5 L

Coverage - 20 sq.m.

This product should not be thinned

Aquatech Preservative Basecoat should be used first on bare timber (2 coats)

Dulux Trade Ultimate Woodstain on top of the basecoat (2-3 coats)

TYPICAL NBS SPECIFICATION

M60 Painting / Clear Finishing - 160 decorative woodstain

This product is associated with the following NBS clauses: M60 Painting/ Clear finishing - 160

This product is associated with the following NBSCreate clause: 45 - 35 - 84/416