

**ARCHITECTURAL STANDARDS
PRODUCT DATA SHEET**

Painting

M60 /Painting / Clear Finishing

M60 / 150

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M60 / 150

MANUFACTURER:

Crown Trade , Crown Trade Paints Ltd

Address

Crown House - Hollins Road, Darwen, Lancasher BB30BG

Tel 0044 (0) 3332227070

E-mail

Website: www.crownpaintspec.co.uk

Supplier: Contact: info@crownpaintspec.co.uk



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Water based primer undercoat

Description: A water based high performance acrylic primer/undercoat

Application: For use over primed metal and as a primer undercoat over joinery and under Crown Interior Acrylic Gloss

Other

Finish : Matt

Drying time: under normal drying conditions touch dry 1 hour and recoatable after 4 hours. Allow for adequate ventilation during the drying period

Limitations: for interior use only . Do not apply when air temperatures fall below 8 degrees centegrade or when relative humidity is above 80% during application or drying periods

Wet film thickness:71 micrometers at 14 sq.m. per litre and dry film thickness:25 micrometres at 14 sq.m. per litre

Packaging: 2.5 litre

TYPICAL NBS SPECIFICATION

M60 Painting / Clear Finishing - 150 Eggshell/ Satin Paint, 110 Emulsion

This product is associated with the following NBS clauses: M60 Painting/ Clear finishing - 150 Eggshell/ Satin Paint, and 110 Emulsion Paint