

Imperial College London



Network modelling of coupled heat transfer and fluid flow at pore-to-mesoscale using MpNM - A Multi-physics Network Model


Mingliang Qu, Martin. J. Blunt, Xiaolei Fan, Qingyang Lin

Imperial College Consortium on Pore-Scale Modelling and Imaging Annual Meeting

Background


 Prediction of properties in large systems (cm scale and above) with complex pore structure is important but challenging in many engineering applications

Large porous media



(a) Natural porous media:

e.g. Thermal energy storage




- (b) Engineering porous media:
- e.g. Packed bed reactor, heat exchanger

Challenges


- Multi-physics processes:
 - Coupled heat and mass transfer
 - Reaction involved
- Pore-scale impacts on large scale:
 - Heterogeneity
 - Preferential transport path
- Large length and time scales
- Complex pore structure
 - Tortuous
 - Irregular
 - ...
- Experimental characterization is difficult

Background

Simulations can obtain more detailed information, but how to cross scales remains unresolved.



How to connect two scales




The computational domain is small (nm~µm), difficult to show macroscopic characteristics

The macro scale model can be used to calculate large scale problems (cm~m), but lose pore-scale detail.

It is essential to develop models to consider pore-scale behaviour and reflect the macroscopic characteristics: Pore-to-mesoscale

Requirement for pore-to-mesoscopic model

Most pore-scale models are designed for applications in the oil and gas industry where the applications are, to some extent, limited.






Flow and displacement

- ✓ Capillary-controlled flow
- ✓ Often rule-based
- ✓ Emphasis on predicting absolute and relative permeability

Pore-scale models need to be more general to study complex processes in porous media in other fields and make a difference, for example, in applications associated with the energy transition.





Multi-physics process:


- √ Steady-state process
- ✓ Transient process
- ✓ Mass transfer
- ✓ Heat transfer
- ✓ Reactive flow

We have developed an open-source Multi-physics Network Model (MpNM) in PYTHON.

- Development of MpNM
- Model validation
- > Application 1
 - Mesoscopic insight in heat and mass transfer
- > Application 2
 - Simulation driven structure optimization a demonstration
- > Application 3
 - Aquifer thermal energy storage

Dual-network

- The network extraction was applied to generate solid and void networks.
- The topological and geometric information for the links connecting the two networks was obtained in order to construct the dual-network



Interfacial areas for heat transfer




Fig.1 3D schematic

Fig.2 2D schematic

$$A_{interface} = \frac{\left(A_{region_1} + A_{region_2} - A_{overall}\right)}{2}$$

where A_{region_1} and A_{region_2} are individual surface area, the overall surface area excluding the interfacial area is $A_{overall}$.

Governing equations

Mass balance
$$\sum_{j=1}^{N_j} g_{ij} (P_i - P_j) = 0$$


- 1. In this work, we considered that the viscosity is a function of fluid temperature and pressure.
- 2. We utilized the local Nusselt number for heat transfer based on local Reynolds number and Prandtl number.
- 3. The h_{sf} was used to calculate the heat transfer between solid and fluid.

 $h_{sf} = \frac{1}{\frac{l_{i,void}}{Nu_{sf}\lambda_f} + \frac{l_{i,solid}}{\beta\lambda_{i,solid}}}$ (Dixon 1979)

- Development of MpNM
- Model validation
- > Application 1
 - Mesoscopic insight in heat and mass transfer
- > Application 2
 - Application 2: Simulation driven structure optimization a demonstration
- > Application 3 (ongoing)
 - Aquifer thermal energy storage

Experimental validation


A bead pack structure has been fabricated which is similar as the experiment from Jiang et al 1999. The local heat transfer coefficient based on various Reynolds number has been studied in this case.



Case description:

- Experimental parameters: 58 x 80 x 5 mm
- Bronze bead diameter: 0.428 mm
- Heat flux: 2 x 10⁵ W/m²
- Entrance temperature: 300 K
- Entrance Reynolds number: 743-4507
- Processes: convection, conduction & single-phase flow

- DEM was used to build bead packed structure.
- Image dimension: 2600x500x250 voxels
- Physical size: 55.64 × 10.70 × 5.35 mm
- Network: 84,597 nodes & 627,805 links



It contains 53,023 beads, which is almost impossible for other pore-scale models.

Boundary conditions for the model

		Boundary condition		values	Initial condition	
Heat transfer	Solid	Neumann	Тор	2×10 ⁵ W/m ²	- 300K	
		Neumann	others	$\nabla T_{\rm s} \cdot {\bf n} = 0$		
	Fluid	Dirichlet	Left	300K	300K	
		Outflow	Right	$\nabla T_f \cdot \mathbf{n} = 0$		
		Neumann	others	$\nabla T_f \cdot \mathbf{n} = 0$		

Heat transfer coefficient


Local heat transfer coefficient:

$$h_{x} = \frac{q_{heat}}{T_{w,x} - T_{f,x}}$$

Mean heat transfer coefficient:

$$h_m = \frac{q_{heat}}{\left(T_{w,m} - T_{f,m}\right)}$$

$$T_{w,m} = \frac{\sum_{i=1}^{N} T_{w,i}}{N}, \qquad T_{f,m} = \frac{\sum_{i=1}^{N} T_{f,i}}{N}$$



For the constant heat flux boundary condition, we build a padding layer to ensure the sufficient heat flux input and set a ω :

$$\omega = \frac{W \cdot L}{\pi \sum_{i=1}^{N} r_i^2}$$

where W and L are the width and length of the boundary surface, N is the number of the padding nodes, and r is the radius of original padding nodes.

11


Simulation results against experimental measurements


Local heat transfer coefficient:


$$h_{x} = \frac{q_{heat}}{T_{w,x} - T_{f,x}}$$


Mean heat transfer coefficient:


$$h_m = \frac{q_{heat}}{\left(T_{w,m} - T_{f,m}\right)}$$















According to the results, we can see:

- 1. The local heat transfer coefficients of our model match experimental results well.
- 2. The average deviation between mean heat transfer coefficients and experimental results is 12%.

- Development of MpNM
- Model validation
- > Application 1
 - Mesoscopic insights into heat and mass transfer
- > Application 2
 - Simulation driven structure optimization a demonstration
- Application 3 (ongoing)
 - Aquifer thermal energy storage

Application 1: Mesoscopic insights into heat and mass transfer




In this case, we studied a typical constant temperature scenario.


Case description:

- Image dimension: 2500 x 500 x 500 voxels (containing 108,213 beads)
- Physical size: 55.64 × 10.70 × 5.35 mm
- Network: 158,592 nodes & 1,164,579 links
- Processes: steady-state, convection, conduction & single-phase flow

		Boundary	condition	values	Initial condition	
Heat transfer	Solid	Dirichlet	Bottom, Top, Front, Back	400K	300K	
		Neumann	others	$\nabla T_{\rm s} \cdot {\bf n} = 0$		
		Dirichlet	Left	300K		
	Fluid	Outflow	Right	$\nabla T_f \cdot \mathbf{n} = 0$	300K	
		Neumann	others	$\nabla T_f \cdot \mathbf{n} = 0$		




- We calculated the average temperature profile of the solid and the fluid phase along the flow direction.
- The low ReD has a higher fluid temperature out than the high ReD.
- The maximum difference in temperature between solid and fluid for high ReD rises with increasing ReD.




- The temperature fields show the node temperature including solid and void.
- The work domain can be divided into 50 blocks along the flow direction.
- We computed the viscosity in each void node as a function of shortest distance to the centre axis along the flow direction on a pore-by-pore basis.
- The viscosity near the inlet and along the centre-line is larger, where the fluid is cooler.

Application 1 Mesoscopic insights into heat and mass transfer



Normalized velocity fields


- The figure shows the normalized velocity fields
 with various Re_D.
- With an increase in Re_D, the velocity fields become more uniform.



Local Reynolds number distribution along the flow direction

We computed the Reynolds number in each void node as a function of shortest distance to the centre axis along the flow direction on a pore-by-pore basis.


Application 1 Mesoscopic insights into heat and mass transfer



- There are existing maximum or minimum values for viscosity slope and Reynolds number slope.
- The viscosity and Re are uniform at the inlet.
- The location of maximum/minimum value for those curves increase with increased Re_D.


- Development of MpNM
- Model validation
- > Application 1
 - Mesoscopic insight in heat and mass transfer
- > Application 2
 - Simulation driven structure design a demonstration
- Application 3 (ongoing)
 - Aquifer thermal energy storage


Application 2: Simulation driven structure design – a demonstration



- We apply a dilation algorithm to the original image (we dilate the spheres and allow them to overlap).
- The porosity and permeability decrease, but the solid-fluid interfacial areas increase. Both curves are non-linear.

Application 2 Simulation driving structure design






- Various constant pressure drops (25-8000 Pa) were set as the boundary conditions to simulate the mass and heat transfer processes and compute the associated mean heat transfer coefficients.
- When entrance velocity is lower than 1×10^{-4} m/s, the thermal conduction is dominant.
- When entrance velocity is higher than 1×10^{-4} m/s, the thermal convection is dominant.

- Development of MpNM
- Model validation
- > Application 1
 - Mesoscopic insight in heat and mass transfer
- > Application 2
 - Simulation driven structure optimization a demonstration
- Application 3 (ongoing)
 - Aquifer thermal energy storage

Application 3: Aquifer thermal energy storage (ongoing)



Common assumptions:


- Homogeneous system
- Same phase temperature
- Constant fluid parameters

Reality:

- Heterogeneous system
- Local thermal nonequilibrium
- Varying fluid parameters

MpNM model:

Based on real-structure, we fabricated a thermal conduction case with length of ~0.4 m and time range ~3 h.



Conclusions

- We developed an approach for fabricating a multi-physics dual-network model.
- > A validation for this model has been made by matching experimental results.
- According to MpNM, we can obtain the temperature and velocity fields node by node.
- > The model shows the capacity for guiding structure design.
- This model is a potential tool in simulating underground thermal energy storage system.
- Future work will extend the model to study reaction, phase change and multiphase flow.

Thank you for listening!

Questions and comments