


Detection and diagnosis of change of condition

ABB Corporate Research Germany, ABB Corporate Research Poland, AGH University of Science and Technology, Cranfield University, Imperial College London


Detection and diagnosis of change of condition



A change of condition in a process or a piece of equipment may be a developing fault or variations in production regimes.

Fault detection and diagnosis determines the occurrence, the type and the severity the undesirable changes.

Research Heterogeneous Outcomes



Multimode methods



Data

Flow rate

Composition

Impact



¥Ξ



Improvements Achieved

Reduced false and missed alarm rates More robust

monitoring systems Easier interpretation

of monitoring results

Wider range of diagnosable faults

Operation log Data fusion

dataset

Tian Cong (AGH/ABB PL, ABB DE)

Bayesian reasoning analysis of fault occurrences using

Ruomu Tan (Cranfield, Imperial/ABB PL)

Kernel based nonlinear condition monitoring for operation under varying production regimes

Abnormal event management with heterogeneous data from

Anna Stief (ABB PL/AGH, Cranfield)

Combining data from disparate sources for


Matthieu Lucke (ABB DE/Imperial)

disparate sources

Improving feature design

Better feature design can increase the robustness & industrial applicability of solutions. New methods were developed:


- Normalizing process measurements using alarm thresholds
- Extracting features in alarm logs or multimode process data
- Ranking and selecting process measurements (using their alarms) or features from electromechanical measurements



Accounting for varying production regimes

Varying production regimes should be distinguished from undesirable changes. This was achieved by:


- Characterizing multimode data using a new localized kernel
- Creating a framework with adaptive clustering & a new kernel
- Identifying varying dynamics using Bayesian Kalman filtering



Combining the heterogeneous data

Combining data from diverse sources improves the reliability & robustness of condition assessments. Methods created for:

- Fusing process measurements and alarm and event logs
- Fusing signals from multiple sensors and acquisition systems
- Fusing process measurements and statistical alarms



Creating the PRONTO heterogeneous benchmark dataset

The PRONTO benchmark dataset was created to meet the need for a benchmark dataset to support development and validation of monitoring techniques with heterogenous data.

The dataset was used in PRONTO and is openly available to the scientific community at doi.org/10.5281/zenodo.1341583.

Data type	Sampling rate	Storage
Process data	1 Hz	Regularly sampled
Alarm and event log	Event-driven	Discrete events
Ultrasonic data	10 kHz	60s recordings
High-frequency pressure	5 kHz	6os recordings
Videos	-	30-60s recordings
	Process data Alarm and event log Ultrasonic data High-frequency pressure	Process data 1 Hz Alarm and event log Event-driven Ultrasonic data 10 kHz High-frequency pressure 5 kHz



The PRONTO Benchmark Dataset contains data

Fully-automated process facility used to generate the PRONTO Benchmark Datase



modelling of change of condition.



New analytics approaches which combine data from heterogeneous sources whilst accounting for varying production regimes improve the detection, diagnosis and

> **Imperial College** London



The research leading to these results has received funding from the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska Curie grant agreement No 675215



